



The quality standard

- 3 year warranty
- Nickel coated finish
- Twin ball race
- Bolt hole castors supplied with axle nut & bolt (plate mounted are riveted)
- Pintle available (sold separately, not factory fitted)

Fork Options

Mount Type	Standard Plate			Bolt Hole	
Fork Size	50 2	50 2	50 2	50 2	50 2
Mount Height	65 2 9/16	65 2 9/16	65 2 9/16	65 2 9/16	65 2 9/16
Swept Radius	47 1 7/8	57 2 1/4	not applicable	47 1 7/8	57 2 1/4

Can be fitted with 3/8" or M10 bolt mounts (with M10 threaded tube ends) or add grip neck pintles (more information on page 80-82)

Wheel Options

Hub Width x Bore	Bearing Type	Capacity	Diameter x Width	Tyre Material (more information) (see p 88-89)	Fork Type	Plate Swivel	Plate Wheel Brake	Plate Fixed	Bolt Hole Swivel	Bolt Hole Wheel Brake
					Wheel Only	/LKP	/LKPBR	/LKF	/LKH	/LKHBR
25x6 1 x 1/4	Plain	30kg 70lb	50x20 2 x 3/4	TPE 	LJP50	LJP50/LKP	LJP50/LKPBR	LJP50/LKF	LJP50/LKH	LJP50/LKHBR
25x6 1 x 1/4	Plain	30kg 70lb	50x20 2 x 3/4	Nylon 	LNN50	LNN50/LKP	LNN50/LKPBR	LNN50/LKF	LNN50/LKH	LNN50/LKHBR

30kg 70lb

L | core