



**new product**

**The quality standard**

- 5 year warranty on fork
- 3 year warranty on wheel
- CoreCoat™ lacquer provides 3 times the Australian Standard for corrosion protection
- Available brass plated as factory special

**Notes:**

- Wheels with roller bearings have a 19mm reduced to 1/2" with axle bush
- Wheels with precision bearings have a 17mm ID reduced to 1/2" with 2 spacer bushes

**Fork Options**

Mount Type	ISO Plate		North American (NA) Plate		Fixed Plate ISO & NA External			
	130 5 1/8"	100 4"	76/67 3 - 2 7/8"	114 4 1/2"	100 4"	125 4 15/16"	150 5 7/8"	200 8"
	11mm 7/16" holes		11mm 7/16" slotted holes		holes as per ISO or NA plate drawing			
	Fitted with Standard ISO plate OUR100/OZPTB for NA plate add N after code OUR100/OZPN <sup>T</sup> B							
	Fitted with Standard ISO plate OUR100/OZF for NA plate add N after code OUR100/OZFN							
Fork Size	100 4	125 5	150 6	200 8	100 4	125 5	150 6	200 8
Mount Height	138 5 7/16	162 6 5/16	189 7 7/16	241 9 1/2	138 5 7/16	162 6 5/16	189 7 7/16	241 9 1/2
Swept Radius	96 3 3/4"	109 4 1/4"	121 4 3/4"	152 6"	142 5 5/8"	142 5 5/8"	161 6 5/16"	161 6 5/16"
	Not applicable - no swivel							

**Wheel Options**

Hub Width x Bore mm / inches	Bearing Type	Capacity kg / lb	Diameter x Tread Width (nominal diameter inches)	Tyre Material (see p 88-89)	Fork Type	Plate Swivel	Plate Total Brake	Plate Directional Lock	Plate Fixed
Wheel Only						/OZP	/OZPTB	/OZPDL	/OZF
60x1/2" 2 3/8x 1/2	Roller	300kg 660lb	100x50 4x2	PU on PP (mech-lock)	OUR100	OUR100/OZP	OUR100/OZPTB	OUR100/OZPDL	OUR100/OZF
60x1/2" 2 3/8x 1/2	Roller	330kg 725lb	125x50 5x2		OUR125	OUR125/OZP	OUR125/OZPTB	OUR125/OZPDL	OUR125/OZF
60x1/2" 2 3/8x 1/2	Roller	360kg 790lb	150x50 6x2		OUR150	OUR150/OZP	OUR150/OZPTB	OUR150/OZPDL	OUR150/OZF
60x1/2" 2 3/8x 1/2	Roller	400kg 880lb	200x50 8x2		OUR200	OUR200/OZP	OUR200/OZPTB	OUR200/OZPDL	OUR200/OZF
60x1/2" 2 3/8x 1/2	Ball	300kg 660lb	100x50 4x2	Grey Rubber	OSQ100	OSQ100/OZP	OSQ100/OZPTB	OSQ100/OZPDL	OSQ100/OZF
60x1/2" 2 3/8x 1/2	Ball	330kg 725lb	125x50 5x2		OSQ125	OSQ125/OZP	OSQ125/OZPTB	OSQ125/OZPDL	OSQ125/OZF
60x1/2" 2 3/8x 1/2	Ball	360kg 790lb	150x50 6x2		OSQ150	OSQ150/OZP	OSQ150/OZPTB	OSQ150/OZPDL	OSQ150/OZF
60x1/2" 2 3/8x 1/2	Ball	400kg 880lb	200x50 8x2		OSQ200	OSQ200/OZP	OSQ200/OZPTB	OSQ200/OZPDL	OSQ200/OZF
60x1/2" 2 3/8x 1/2	Ball	300kg 660lb	100x50 4x2	Hi-res Blue Rubber	OBQ100	OBQ100/OZP	OBQ100/OZPTB	OBQ100/OZPDL	OBQ100/OZF
60x1/2" 2 3/8x 1/2	Ball	330kg 725lb	125x50 5x2		OBQ125	OBQ125/OZP	OBQ125/OZPTB	OBQ125/OZPDL	OBQ125/OZF
60x1/2" 2 3/8x 1/2	Ball	360kg 790lb	150x50 6x2		OBQ150	OBQ150/OZP	OBQ150/OZPTB	OBQ150/OZPDL	OBQ150/OZF
60x1/2" 2 3/8x 1/2	Ball	400kg 880lb	200x50 8x2		OBQ200	OBQ200/OZP	OBQ200/OZPTB	OBQ200/OZPDL	OBQ200/OZF
60x1/2" 2 3/8x 1/2	Roller	120kg 265lb	100x43 4x1 11/16	Rubber on Cast Iron	OOR100	OOR100/OZP	OOR100/OZPTB	OOR100/OZPDL	OOR100/OZF
60x1/2" 2 3/8x 1/2	Roller	180kg 395lb	125x43 5x1 11/16		OOR125	OOR125/OZP	OOR125/OZPTB	OOR125/OZPDL	OOR125/OZF
60x1/2" 2 3/8x 1/2	Roller	210kg 460lb	150x43 6x1 11/16		OOR150	OOR150/OZP	OOR150/OZPTB	OOR150/OZPDL	OOR150/OZF
60x1/2" 2 3/8x 1/2	Roller	250kg 550lb	200x43 8x1 11/16		OOR200	OOR200/OZP	OOR200/OZPTB	OOR200/OZPDL	OOR200/OZF
60x1/2" 2 3/8x 1/2	Plain	350kg 770lb	100x40 4x 1 9/16	Nylon	ONA100	ONA100/OZP	ONA100/OZPTB	ONA100/OZPDL	ONA100/OZF
60x1/2" 2 3/8x 1/2	Roller	350kg 770lb	100x40 4x 1 9/16		ONR100	ONR100/OZP	ONR100/OZPTB	ONR100/OZPDL	ONR100/OZF
60x1/2" 2 3/8x 1/2	Plain	380kg 835lb	125x40 5x 1 9/16		ONA125	ONA125/OZP	ONA125/OZPTB	ONA125/OZPDL	ONA125/OZF
60x1/2" 2 3/8x 1/2	Roller	380kg 835lb	125x40 5x 1 9/16		ONR125	ONR125/OZP	ONR125/OZPTB	ONR125/OZPDL	ONR125/OZF
60x1/2" 2 3/8x 1/2	Plain	400kg 880lb	150x40 6x 1 9/16		ONA150	ONA150/OZP	ONA150/OZPTB	ONA150/OZPDL	ONA150/OZF
60x1/2" 2 3/8x 1/2	Roller	400kg 880lb	150x40 6x 1 9/16		ONR150	ONR150/OZP	ONR150/OZPTB	ONR150/OZPDL	ONR150/OZF
60x1/2" 2 3/8x 1/2	Plain	400kg 880lb	200x40 8x 1 9/16		ONA200	ONA200/OZP	ONA200/OZPTB	ONA200/OZPDL	ONA200/OZF
60x1/2" 2 3/8x 1/2	Roller	400kg 880lb	200x40 8x 1 9/16		ONR200	ONR200/OZP	ONR200/OZPTB	ONR200/OZPDL	ONR200/OZF

**120-400kg 265-880lb**

**core**