

Fittings for Supertanks

Specialised polyethylene extrusion welding and fusion welding techniques ensure all Superior Pak Supertank fittings can be positioned to suit your exact requirements. Our high quality range includes BSP, ANSI 150, Full Face, Backing Plates and drill patterns to suit, with Superior Pak representatives able to assist you with your selection and compliance requirements.



Full Face Flange



Stub with Backing Plate



Manhole Cover

Flanges Full Face

Code No.	Description
P287350	25 mm Full Face Flange
P287380	32 mm Full Face Flange
P287490	38 mm Full Face Flange
P288050	50 mm Full Face Flange
P288180	65 mm Full Face Flange
P288890	80 mm Full Face Flange
P289250	100 mm Full Face Flange
P290050	150 mm Full Face Flange
P290450	200 mm Full Face Flange

Flange Backing Plates

Code No.	Description
P287290	25 mm Stub with Backing Plate
P287450	32 mm Stub with Backing Plate
P287510	38 mm Stub with Backing Plate
P288010	50 mm Stub with Backing Plate
P288160	65 mm Stub with Backing Plate
P288870	80 mm Stub with Backing Plate
P289290	100 mm Stub with Backing Plate

Manhole Covers

Code No.	Description
P391000	250 mm Inspection Cover with Vent
P391400	300 mm Inspection Cover with Vent
P391800	450 mm Manhole Cover with Vent
P392000	620 mm Manhole Cover with Vent



Valves

Code No.	Description
P534110	12 mm Ball Valve
P534610	18 mm Ball Valve
P535110	25 mm Ball Valve
P535600	32 mm Ball Valve
P536200	38 mm Ball Valve
P537410	50 mm Ball Valve

Outlets & Backnuts

Code No.	Description
P418400	18 mm Male Outlet & Backnut
P419600	25 mm Male Outlet & Backnut
P420200	32 mm Male Outlet & Backnut
P420900	38 mm Male Outlet & Backnut
P421600	50 mm Male Outlet & Backnut

Female Fused Outlets

Code No.	Description
P417900	18 mm Female Fused Outlet (BSP)
P419500	25 mm Female Fused Outlet (BSP)
P420000	32 mm Female Fused Outlet (BSP)
P420800	38 mm Female Fused Outlet (BSP)
P421500	50 mm Female Fused Outlet (BSP)
P422400	75 mm Female Fused Outlet (BSP)

Male Fused Outlets

Code No.	Description
P418010	18 mm Male Fused Outlet (BSP)
P419400	25 mm Male Fused Outlet (BSP)
P420110	32 mm Male Fused Outlet (BSP)
P420600	38 mm Male Fused Outlet (BSP)
P421400	50 mm Male Fused Outlet (BSP)
P422300	75 mm Male Fused Outlet (BSP)

Level Indicator Assembly

Code No.	Description
P378810	Ball Float Level Indicator Assembly

Sight Glass Assembly

Code No.	Description
P186510	Sight Glass Assembly c/w Clear PVC Tube & Safety Ball Valve

Tap Connection

Code No.	Description
P519050	18 mm Tap BSP 18mm Female Outlet & Backnut

Anchoring Points

Code No.	Description
E1294-G02	Anchoring Point (one point)



Male Fused Outlet



Female Fused Outlet



Anchoring Point



Tap Connector



Outlet & Backnut



Ball Valve



Level Indicator



Sight Glass