

## FE Fork Extension Slippers

- Made of High Tensile Grade Steel
- Zinc Plated for added Protection
- High Safe Working Load (SWL) Rating
- Supplied with Toggle Locking Pins
- Fitted with Rating Plate
- Supplied with Instructions



The type FE Fork Extension Slippers have been designed with a slim profile to extend the versatility of your Lift Truck. These Slippers have been designed and manufactured in accordance with AS2359.15.

In accordance with AS2359.15 Slippers used for general usage should be no longer than 167% of the supporting Tine's length. If the Slippers are longer than 167%, then the usage of those Slippers shall be restricted to their specified application.



Type	Length (mm)	To suit max tine size (mm)	Weight per pair (kg)	Rating per pair
FE1-16	1600	100 x 45	50	3000kg
FE1-18	1800	100 x 45	56	SWL
FE1-21	2100	100 x 45	66	at
FE1-24	2400	100 x 45	75	600mm LC
FE2-16	1600	130 x 50	60	4500kg
FE2-18	1800	130 x 50	66	SWL
FE2-21	2100	130 x 50	78	at
FE2-24	2400	130 x 50	88	600mm LC
FE3-16	1600	155 x 55	91	6500kg
FE3-18	1800	155 x 55	102	SWL
FE3-21	2100	155 x 55	119	at
FE3-24	2400	155 x 55	136	600mm LC
FE3-30	3000	155 x 55	170	

Type	Length (mm)	To suit max tine size (mm)	Weight per pair (kg)	Rating per pair
FE4-18	1800	160 x 65	133	8500kg
FE4-21	2100	160 x 65	155	SWL
FE4-24	2400	160 x 65	177	at
FE4-30	3000	160 x 65	221	600mm LC
SL5-18	1800	Custom	170	8000kg
SL5-21	2100	built	200	SWL
SL5-24	2400	to	220	at
SL5-30	3000	suit	280	600mm LC
SL6-21	2100	Custom	380	12000kg
SL6-24	2400	built	430	SWL
SL6-30	3000	to	540	at
SL6-35	3500	suit	630	600mm LC
SL7-24	2400	Custom	520	16000kg
SL7-30	3000	built to	650	SWL at
SL7-35	3500	suit	760	600mm LC

We Gladly Accept



*Proudly distributed by*

**RJ Cox Engineering**

[www.coxengineering.com.au](http://www.coxengineering.com.au)  
[info@coxengineering.com.au](mailto:info@coxengineering.com.au)

Ph: 02) 9114 6867  
 Fax: 02) 9486 3009