



R J COX ENGINEERING
A Division of E W Cox Pty Ltd
ABN 69 000 098 484

Standard Pallet Trucks

Hytsu 2500Kg Standard Pallet Trucks

- Use for Standard "Chep" pallet width
- Three position hand lever
- Hard chrome plated lift ram and pump lever
- Double ball bearings on each wheel
- Choice of Nylon or Polyurethane wheels

Options

- Quick Lift ram - only 4 to 5 pumps to full height
- Three different widths – 685mm, 520mm & 450mm
- Two different Lengths – 1150mm & 915mm



Rhino Hand Pallet Trucks

- Highest Quality ideal for Heavy Users
- Rhino adjustable Solid Steel Push Rods
- Reinforced Constructions
- Rhino Hand Pallet Trucks are supplied with greased nipples and bushes on all necessary pivot points
- Zinc coated axles
- Spacer rollers standard on all Rhino Hand Pallet Trucks
- Nylon wheels standard; polyurethane available upon request
- Entry rollers



We Gladly Accept



RJ Cox Engineering

www.coxengineering.com.au
info@coxengineering.com.au

Ph: 02) 9114 6867
Fax: 02) 9486 3009



R J COX ENGINEERING
A Division of E W Cox Pty Ltd
ABN 69 000 098 484

Special Pallet Trucks

"Low Boy" Pallet Trucks - Standard Length 1150mm

2500Kg Capacity Low Profile 65mm high
NR25LL - Standard 685mm wide
NR25SL - Medium 520mm wide

2000Kg Extra Low Profile 51mm high
NR20NLM - Standard width 685mm wide

1000Kg Extra Extra Low Profile 35mm high
NR10NLV - Standard 685mm wide
NR10NSV - Medium 520mm wide



High Capacity Hytsu Pallet Trucks - Standard Length 1150mm

NR30NL – 3000kg	Standard Width 685mm
NR30NLQ - 3000kg	Standard Width 685mm Quick Lift
NR30NS - 3000kg	Medium Width 520mm
NR30NN - 3000kg	Narrow Width 450mm
NR50NL - 5000kg	Standard Width 685mm
NR50NS - 5000kg	Medium Width 520mm

2000kg Wide Pallet Trucks - Standard Length 1150mm

- Various Options available - see Standard Pallet Truck Options
- Nylon or Polyurethane wheels
- Often only available ex factory

NR20NLXL800 Width 800mm Dimensions (800mm x 1150mm x 85mm)
NR20NLXL830 Width 830mm Dimensions (830mm x 1150mm x 85mm)
NR20NLXL830SQ Width 830mm Dimensions (830mm x 1000mm x 85mm) **Quick Lift***
NR20NLXL900 Width 900mm - Dimensions (900mm x 1150mm x 85mm)
NR20NLXL1000 Width 1000mm - Dimensions (1000mm x 1150mm x 85mm)
NR20NLXL1100 Width 1100mm - Dimensions (1100mm x 1150mm x 85mm)
NR20NLXL1200 Width 1200mm - Dimensions (1200mm x 1150mm x 85mm)
NR20NLXL1300 Width 1300mm - Dimensions (1300mm x 1150mm x 85mm)
NR20NLXL1400 Width 1400mm - Dimensions (1400mm x 1150mm x 85mm)
NR20NLXL1500 Width 1500mm - Dimensions (1500mm x 1150mm x 85mm)


*Non Standard Length - 1000mm

2000kg Long Hand Pallet Trucks

- Various Options available - see Standard Pallet Truck Options
- Nylon or Polyurethane wheels
- Often only available ex factory
- Available 685mm or 520mm Wide

Lengths Available 1200mm, 1300mm, 1400mm, 1500mm, 1600mm, 1700mm, 1800mm, 1900mm, 2000mm, 2100mm, 2200mm, 2300mm, 2400mm



 **HYTSU** The No.1 Force in Pallet Tracks



RJ Cox Engineering
www.coxengineering.com.au
info@coxengineering.com.au

Ph: 02) 9114 6867
Fax: 02) 9486 3009

Anti Corrosion Pallet Trucks

Anti corrosion models are deigned to work in areas with high levels of salt/fresh water, chemicals or other harsh applications.

Stainless Steel Hand Pallet Trucks - Anti Corrosion Abilities fitted with Stainless Steel Bearings Axles & Body, all parts made of stainless steel

Options Include

- Standard Width & Length
- Narrow Width 520mm Wide
- 51mm Extra Low profile rated to 2000Kg
- 65mm Low profile rated to 2500Kg
- Galvanised Hand Pallet Trucks



Hot Dipped Galvanised Body - Chrome Ram and Zinc plated pump Supplied with Nylon wheels Stainless Steel Bearings & Axles

Options Include

- Standard Width 685mm Wide
- Extra low 51mm profile 2000Kg
- Low profile 65mm 2500Kg
- High Capacity 3000Kg
- Narrow Width 520mm Wide
- High Capacity 3000kg's


Various Options Available

Hand brake fitted on rear steer wheels with lever on hand guard to provide extra braking facility under load.

Rubber Tyred Steer Wheel on Aluminium centre fitted in lieu of nylon or poly wheels

Tandem Load Wheels fitted to improve movement over rough or undulating surfaces



 **The No.1 Force in Pallet Tracks**



RJ Cox Engineering
www.coxengineering.com.au
info@coxengineering.com.au

Ph: 02) 9114 6867
Fax: 02) 9486 3009

Special Models Pallet Trucks

TY33 - Drum Handling Pallet Truck

Specially designed pallet truck for handling drums, etc.
 Capacity 330Kg

- Specialised design for holding drums
- Dimensions (730mm x 1080mm x 1215mm)



NR25NW - Weight Scale Pallet Truck

2500kg capacity hand pallet truck with weight gauge.
 Weight gauge to max 2000kg capacity.

- Weight accuracy + or - 0.1Kg for 2000Kg load
- Proven METTLER TOLEDO scale
- Dimensions (700mm x 1150mm x 90mm)



Forklift Jacks & Stands

HFJ40 4 tonne Hydraulic Forklift Jack

- Single Support Point
- Starting height 65mm
- Max lifting height 425mm
- Max strokes to full height 30-60



HFJ50 5 tonne Hydraulic Forklift Jack

- Double Support Points
- Starting height at low/hi positions 65mm/415mm
- Max lifting height at low/hi positions 425mm/725mm
- Max strokes to full height 30-60



HFJ65S & HFJ110 Forklift Stands

2 models - 6.5 tonne capacity & 11 tonne capacity come as a pair

Adjusting range 240mm - 410mm

Capacity per stand 6500kg/11000kg or double for two stands



We Gladly Accept



RJ Cox Engineering
www.coxengineering.com.au
info@coxengineering.com.au

Ph: (02) 9114 6867
 Fax: (02) 9486 3009