

## Standard Pallet Trucks

### Xilin 2500kg Hand Pallet Truck

- 2500Kg's Max Lift Capacity
- 200mm Diameter Urethane Steer Wheels
- Rubber Coated Comfort Handle
- Number of Pump Strokes - 10 to Max Lift
- 200mm Max Lift Height
- WBF685SPW - 685x1150x85mm
- WBF520SPW - 520x1150x85mm



### Hytsu 2500Kg Standard Pallet Trucks

- Use for Standard "Chep" pallet width
- Three position hand lever
- Hard chrome plated lift ram and pump lever
- Double ball bearings on each wheel
- Choice of Nylon or Polyurethane wheels

#### Options

- Quick Lift ram - only 4 to 5 pumps to full height
- Three different widths – 685mm, 520mm & 450mm
- Two different Lengths – 1150mm & 915mm



### Rhino Hand Pallet Trucks

- Highest Quality ideal for Heavy Users
- Rhino adjustable Solid Steel Push Rods
- Reinforced Constructions
- Rhino Hand Pallet Trucks are supplied with greased nipples and bushes on all necessary pivot points
- Zinc coated axles
- Spacer rollers standard on all Rhino Hand Pallet Trucks
- Nylon wheels standard; polyurethane available upon request
- Entry rollers



We Gladly Accept



**RJ Cox Engineering**  
[www.coxengineering.com.au](http://www.coxengineering.com.au)  
[info@coxengineering.com.au](mailto:info@coxengineering.com.au)

Ph: 02) 9114 6867  
Fax: 02) 9486 3009



R J COX ENGINEERING  
A Division of E W Cox Pty Ltd  
ABN 69 000 098 484

## Special Pallet Trucks

### "Low Boy" Pallet Trucks - Standard Length 1150mm

2500Kg Capacity Low Profile 65mm high  
NR25LL - Standard 685mm wide  
NR25SL - Medium 520mm wide

2000Kg Extra Low Profile 51mm high  
NR20NLM - Standard width 685mm wide

1000Kg Extra Extra Low Profile 35mm high  
NR10NLV - Standard 685mm wide  
NR10NSV - Medium 520mm wide



### High Capacity Hytsu Pallet Trucks - Standard Length 1150mm

NR30NL - 3000kg	Standard Width 685mm
NR30NLQ - 3000kg	Standard Width 685mm <b>Quick Lift</b>
NR30NS - 3000kg	Medium Width 520mm
NR30NN - 3000kg	Narrow Width 450mm
NR50NL - 5000kg	Standard Width 685mm
NR50NS - 5000kg	Medium Width 520mm

### 2000kg Wide Pallet Trucks - Standard Length 1150mm

- Various Options available - see Standard Pallet Truck Options
- Nylon or Polyurethane wheels
- Often only available ex factory

NR20NLXL800 Width 800mm Dimensions (800mm x 1150mm x 85mm)  
NR20NLXL830 Width 830mm Dimensions (830mm x 1150mm x 85mm)  
NR20NLXL830SQ Width 830mm Dimensions (830mm x 1000mm x 85mm) **Quick Lift\***  
NR20NLXL900 Width 900mm - Dimensions (900mm x 1150mm x 85mm)  
NR20NLXL1000 Width 1000mm - Dimensions (1000mm x 1150mm x 85mm)  
NR20NLXL1100 Width 1100mm - Dimensions (1100mm x 1150mm x 85mm)  
NR20NLXL1200 Width 1200mm - Dimensions (1200mm x 1150mm x 85mm)  
NR20NLXL1300 Width 1300mm - Dimensions (1300mm x 1150mm x 85mm)  
NR20NLXL1400 Width 1400mm - Dimensions (1400mm x 1150mm x 85mm)  
NR20NLXL1500 Width 1500mm - Dimensions (1500mm x 1150mm x 85mm)


\*Non Standard Length - 1000mm

### 2000kg Long Hand Pallet Trucks

- Various Options available - see Standard Pallet Truck Options
- Nylon or Polyurethane wheels
- Often only available ex factory
- Available 685mm or 520mm Wide

Lengths Available 1200mm, 1300mm, 1400mm, 1500mm, 1600mm, 1700mm, 1800mm, 1900mm, 2000mm, 2100mm, 2200mm, 2300mm, 2400mm



 **The No.1 Force in Pallet Tracks**



**RJ Cox Engineering**  
[www.coxengineering.com.au](http://www.coxengineering.com.au)  
[info@coxengineering.com.au](mailto:info@coxengineering.com.au)

Ph: 02) 9114 6867  
Fax: 02) 9486 3009

## Anti Corrosion Pallet Trucks

Anti corrosion models are deigned to work in areas with high levels of salt/fresh water, chemicals or other harsh applications.

**Stainless Steel Hand Pallet Trucks** - Anti Corrosion Abilities fitted with Stainless Steel Bearings Axles & Body, all parts made of stainless steel

*Options Include*

- Standard Width & Length
- Narrow Width 520mm Wide
- 51mm Extra Low profile rated to 2000Kg
- 65mm Low profile rated to 2500Kg
- Galvanised Hand Pallet Trucks



**Hot Dipped Galvanised Body** - Chrome Ram and Zinc plated pump Supplied with Nylon wheels Stainless Steel Bearings & Axles

*Options Include*

- Standard Width 685mm Wide
- Extra low 51mm profile 2000Kg
- Low profile 65mm 2500Kg
- High Capacity 3000Kg
- Narrow Width 520mm Wide
- High Capacity 3000kg's


## Various Options Available

**Hand brake** fitted on rear steer wheels with lever on hand guard to provide extra braking facility under load.

**Rubber Tyred Steer Wheel** on Aluminium centre fitted in lieu of nylon or poly wheels

**Tandem Load Wheels** fitted to improve movement over rough or undulating surfaces



 **The No.1 Force in Pallet Tracks**



**RJ Cox Engineering**  
[www.coxengineering.com.au](http://www.coxengineering.com.au)  
[info@coxengineering.com.au](mailto:info@coxengineering.com.au)

Ph: 02) 9114 6867  
Fax: 02) 9486 3009

## Special Models Pallet Trucks

**NR20R 2000Kg Paper Roll Pallet Truck** - Specially designed for handling paper rolls, carpet, etc.

- Specialised tyne design for holding rolls
- Dimensions (865mm x 1220mm x 160mm)
- Custom sizes can be ordered ex factory

### TY33 - Drum Handling Pallet Truck

Specially designed pallet truck for handling drums, etc.  
 Capacity 330Kg

- Specialised design for holding drums
- Dimensions (730mm x 1080mm x 1215mm)

### NR25NW - Weight Scale Pallet Truck

2500kg capacity hand pallet truck with weight gauge.  
 Weight gauge to max 2000kg capacity.

- Weight accuracy + or - 0.1Kg for 2000Kg load
- Proven METTLER TOLEDO scale
- Dimensions (700mm x 1150mm x 90mm)



## Forklift Jacks & Stands

### HFJ40 4 tonne Hydraulic Forklift Jack

- Single Support Point
- Starting height 65mm
- Max lifting height 425mm
- Max strokes to full height 30-60

### HFJ50 5 tonne Hydraulic Forklift Jack

- Double Support Points
- Starting height at low/hi positions 65mm/415mm
- Max lifting height at low/hi positions 425mm/725mm
- Max strokes to full height 30-60

### HFJ65S & HFJ110 Forklift Stands

2 models - 6.5 tonne capacity & 11 tonne capacity come as a pair

Adjusting range 240mm - 410mm

Capacity per stand 6500kg/11000kg or double for two stands

